DCS300 5700lm 34W 730 I TC1 CAT IC0

Asymmetric · 3000K · IP66 · IK09 · RAL 7035,DB703



APPLICATION

Catenary luminaire is designed for suspended installation on a tensioned cable, providing an efficient solution for urban areas where traditional pole-mounted lighting is not suitable. Robust aluminium housing, adjustable mounting bracket and modern LED technology ensure reliable operation, high lighting efficiency and easy installation. Applications: streets, pedestrian zones, city centres, squares, parks, promenades, historical areas and other urban public spaces.

5700 lm	34 W	168 lm/W	3000K	≥70	IP66	IK09	100 000 h
SYSTEM FLUX	INPUT POWER	EFFICACY	CCT	CRI	INGRESS	IMPACT	L90B10

ELECTRICAL PARAMETERS

Nominal supply voltage	**230 (220–240) V AC**	Supply voltage range	**198–264 V AC**
Type of supply current	**AC**	Supply frequency	**50–60 Hz**
Rated input power	**34W**	Power factor (PF)	**0.99**
Driver efficiency at nominal load	**92%**	Total harmonic distortion (THDi)	**<6%**
Protection class (electric shock)	**I**	Surge protection (CM / DM)	**6/10 kV**
Inrush current / time	**35.4A/122µs**	Driver type	**Philips Xitanium**
Number of luminaires on MCB 16A type B	**<30**		

PHOTOMETRIC PARAMETERS

Luminous flux — system	**5700lm**	Luminous flux — LED module	**6500lm**
Luminous efficacy — system	**168lm/W**	Correlated colour temperature (CCT)	**3000K**
Colour rendering index Ra (CRI)	**≥70**	Init. CRI tolerance	**±3**
Light distribution type	**Asymmetric**	Luminaire beam spread	**Wide beam**
Optic type	**Catenary narrow**	Light output ratio (LOR)	**0.87**
Photobiological safety class	**RG1**	Flicker — Output PstLM / SVM	**≤ 0.8 / ≤ 0.1**
Colour consistency (SDCM)	**< 3 MacAdam steps**	Upward light output ratio (ULOR)	**0**
Luminous flux tolerance	**±5 %**		

CONSTRUCTION & MATERIALS

Luminaire type	**Street**	Light source type	**LED**
Light source replaceable	**yes**	Cap / base type	**Integrated**
Housing material	**Aluminium alloy**	Housing coating	**Powder coating**
Optic material	**PMMA**	Optical cover material	**Tempered flat glass**
Housing colour (RAL)	**RAL 7035,DB703**	Mounting type	**Suspended on the rope**
Cutout size	**N/A**	Overall dimensions (H × W × L)	**500x500x286mm**
Weight (net)	**7.5kg**	Windage projection area (side / below)	**0,020 sq.m/ 0,785 sq.m**
Number of light sources	**2 pcs**	Number of gear units	**1 pcs**

PROTECTION & ENVIRONMENT

IP rating — enclosure	**IP66**	Impact resistance class IK	**IK09**
Operating temperature range	**-40...+35 °C**	Storage temperature range	**-40...+65 °C**
Glow-wire test	**650 °C / 5 s**	Relative humidity (max)	**N/A**

CONTROL & DIMMING

Dimmable	**YES**	Control protocol / interface	**on/off**
Dimming range	**10-100%**	Auto-dimming (chronoSTEP)	**Yes, 5 step**
Built-in motion / presence sensor	**On request**	Built-in daylight sensor	**On request**
LED lumen maintenance compensation (CLO)	**Available, On request**	ZHAGA / NEMA socket compatibility	**Available on request. Up and down**

RELIABILITY & LIFETIME

Constant Light Output (CLO)	**Available, On request**	Light source lifetime	**100000@L90 B10h**
Lumen maintenance @ 50 000 h	**L95B5**	Lumen maintenance @ 100 000 h	**L90 B10**
Control gear failure rate @ 50 000 h	**5 %**	Control gear failure rate @ 100 000 h	**10%**
Maximum case temperature Tc	**75°C**		

CERTIFICATIONS

Warranty period	**5 years**	CE marking	**CE marked**
ENEC mark	**No**	ENEC+ mark	**No**
UKCA marking	**UKCA marked**	D4i certified (DALI)	**No**
EU RoHS compliant	**Yes**	Light source energy efficiency class	**C**

STANDARDS & SUSTAINABILITY

Applicable standard	**EN-IEC 62722-2-2**	Application areas	**Streets, city centres, yards and squares.**

Environmental data. Embedded carbon, recyclable content and sustainability ratings are provided per article where determined.

Documents. Photometric files (IES / LDT) and installation instructions are available at takton.ee.