

DKF294 26000LM 172W 740 I RS20D IC0

Symmetric · 4000K · IP66 · IK09 · RAL 7024

Length **532 mm****APPLICATION**

DKF 294 Odin Gen2 L is a powerful and energy-efficient LED floodlight designed for large parking areas, industrial and logistics sites, outdoor sports facilities, building façades and advertising structures. Its slim die-cast aluminium housing combines high light output with a discreet appearance, while the adjustable mounting bracket allows precise aiming from walls, poles and supporting structures. A wide selection of symmetrical and asymmetrical optics enables accurate light distribution for different applications. The available optics make the floodlight suitable for sports grounds, recreational courts and training areas, as well as parking spaces, industrial yards, façades and large advertising banners. Effective optical control helps deliver the required illumination while limiting unnecessary spill light. With a luminous flux of up to 25,000 lm and an efficacy of up to 150 lm/W, Odin Gen2 provides powerful illumination with efficient energy use. The IP66 and IK08 construction, tempered glass cover and Philips Xitanium outdoor driver ensure reliable operation in demanding outdoor environments. Different colour temperatures are available for functional, sports and architectural lighting projects.

26000 lm SYSTEM FLUX	172 W INPUT POWER	151 lm/W EFFICACY	4000K CCT	≥70 CRI	IP66 INGRESS	IK09 IMPACT	100 000 h L90B10
--------------------------------	-----------------------------	-----------------------------	---------------------	-------------------	------------------------	-----------------------	----------------------------

ELECTRICAL PARAMETERS

Nominal supply voltage	230 (220–240) V AC	Supply voltage range	198–264 V AC
Type of supply current	AC	Supply frequency	50–60 Hz
Rated input power	172W	Power factor (PF)	0.98
Driver efficiency at nominal load	93%	Total harmonic distortion (THDi)	10.00%
Protection class (electric shock)	I	Surge protection (CM / DM)	6/10 kV
Inrush current / time	40A 652μsec	Driver type	TCI
Number of luminaires on MCB 16A type B	<4		

PHOTOMETRIC PARAMETERS

Luminous flux — system	26000lm	Luminous flux — LED module	30588lm
Luminous efficacy — system	151lm/W	Correlated colour temperature (CCT)	4000K
Colour rendering index Ra (CRI)	≥70	Init. CRI tolerance	±4
Light distribution type	Symmetric	Luminaire beam spread	20° narrow
Optic type	Rotationally symmetrical	Light output ratio (LOR)	0.89
Photobiological safety class	RG1	Flicker — Output PstLM / SVM	Not specified by the driver manufacturer
Colour consistency (SDCM)	< 3 MacAdam steps	Upward light output ratio (ULOR)	0
Luminous flux tolerance	±5 %		

CONSTRUCTION & MATERIALS

Luminaire type	Floodlight	Light source type	LED
Light source replaceable	yes	Cap / base type	Integrated
Housing material	Aluminium alloy	Housing coating	Powder coating
Optic material	PMMA	Optical cover material	Tempered flat glass
Housing colour (RAL)	RAL 7024	Mounting type	U-shape mounting bracket fixed with standard bolts and nuts.
Cutout size	N/A	Overall dimensions (H × W × L)	532x347x68mm
Weight (net)	8.5kg	Effective projected area	At horizontal position 0.052
Number of gear units	1 pcs		

PROTECTION & ENVIRONMENT

IP rating — enclosure	IP66	Impact resistance class IK	IK09
Operating temperature range	-40...+35 °C	Storage temperature range	-40...+65 °C
Glow-wire test	650 °C / 5 s	Relative humidity (max)	N/A

CONTROL & DIMMING

Dimmable	On/off	Control protocol / interface	DALI,CASAMBI, D4i on request
Auto-dimming (chronoSTEP)	Yes, 5 step	Built-in motion / presence sensor	On request
Built-in daylight sensor	On request	LED lumen maintenance compensation (CLO)	Available, On request

RELIABILITY & LIFETIME

Constant Light Output (CLO)	Available, On request	Light source lifetime	100000@L90 B10h
Lumen maintenance @ 50 000 h	L95B5	Lumen maintenance @ 100 000 h	L90 B10
Control gear failure rate @ 50 000 h	5 %	Control gear failure rate @ 100 000 h	10%
Maximum case temperature Tc	75°C		

CERTIFICATIONS

Warranty period	5 years	CE marking	CE marked
ENEC mark	No	ENEC+ mark	No
UKCA marking	UKCA marked	D4i certified (DALI)	No
EU RoHS compliant	Yes		

STANDARDS & SUSTAINABILITY

Applicable standard	EN-IEC 62722-2-2	ETIM Class	Not determined
Recyclable content ratio	Not determined	Non-virgin material ratio	Not determined
Sustainability rating	Not determined	EAN / UPC	Not determined
Application areas	Sports grounds, parking areas, industrial sites, large outdoor areas		

Environmental data. Embedded carbon, recyclable content and sustainability ratings are provided per article where determined.

Documents. Photometric files (IES / LDT) and installation instructions are available at takton.ee.