DCW214 120 3150lm 19W 840 I PC IP66

Symmetric · 4000 K · IP66 · IK10 · RAL 7035



APPLICATION

DCW214 Series is a modern high-performance waterproof LED luminaire combining a slim, stylish design with high efficiency, durability and easy installation. Its robust polycarbonate housing, stainless steel clips and high-quality European electrical components ensure reliable IP65/IP66 protection and long service life. Quick installation, efficient wide-beam light distribution and multiple lumen, control and through-wiring options make DCW214 an ideal solution for car parks, garages, basements, production areas, warehouses and general lighting applications.

3150 lm	19 W	166 lm/W	4000 K	≥80	IP66	IK10	>100 000 h
SYSTEM FLUX	INPUT POWER	EFFICACY	CCT	CRI	INGRESS	IMPACT	L90B10

ELECTRICAL PARAMETERS

Nominal supply voltage	**230 (220–240) V AC**	Supply voltage range	**198–264 V AC**
Type of supply current	**AC**	Supply frequency	**50–60 Hz**
Rated input power	**19W**	Power factor (PF)	**0.95**
Driver efficiency at nominal load	**92%**	Total harmonic distortion (THDi)	**< 10% @ full load**
Protection class (electric shock)	**I**	Surge protection (CM / DM)	**4/2 kV**
Driver type	**TCI**	Number of luminaires on MCB 16A type B	**45**

PHOTOMETRIC PARAMETERS

Luminous flux — system	**3150lm**	Luminous flux — LED module	**3500lm**
Luminous efficacy — system	**166lm/W**	Correlated colour temperature (CCT)	**4000 K**
Colour rendering index Ra (CRI)	**≥80**	Init. CRI tolerance	**±3**
Light distribution type	**Symmetric**	Luminaire beam spread	**120.0°**
Optic type	**N/A**	Light output ratio (LOR)	**0,90**
Photobiological safety class	**RG0**	Flicker — Output PstLM / SVM	**≤0.1 / ≤0.3**
Colour consistency (SDCM)	**< 3 MacAdam steps**	Upward light output ratio (ULOR)	**N/A**
Luminous flux tolerance	**±5 %**		

CONSTRUCTION & MATERIALS

Luminaire type	**Dust/Waterproof**	Light source type	**LED**
Light source replaceable	**yes**	Cap / base type	**Integrated**
Housing material	**Polycarbonate**	Reflector material	**N/A**
Housing coating	**N/A**	Optic material	**PC**
Optical cover material	**N/A**	Housing colour (RAL)	**RAL 7035**
Mounting type	**Surface, suspended**	Cutout size	**N/A**
Overall dimensions (H × W × L)	**90x102x1174**	Weight (net)	**2.1kg**
Effective projected area	**N/A**	Windage projection area (side / below)	**N/A**
Number of light sources	**1pcs**	Number of gear units	**1 pcs**

PROTECTION & ENVIRONMENT

IP rating — enclosure	**IP66**	Impact resistance class IK	**IK10**
Operating temperature range	**-40...+35 °C**	Storage temperature range	**-40...+50 °C**
Glow-wire test	**650 °C / 5 s**	Relative humidity (max)	**N/A**

CONTROL & DIMMING

Dimmable	**No**	Control protocol / interface	**on/off**
Dimming range	**N/A**	Built-in motion / presence sensor	**on request**

RELIABILITY & LIFETIME

Light source lifetime	**>100000 @ L90 B10 h**	Lumen maintenance @ 50 000 h	**L98 B5**
Lumen maintenance @ 100 000 h	**L90 B10**	Control gear failure rate @ 50 000 h	**5 %**
Control gear failure rate @ 100 000 h	**10 %**	Maximum case temperature Tc	**75°C**

CERTIFICATIONS

Warranty period	**5 years**	CE marking	**Yes**
ENEC mark	**No**	ENEC+ mark	**No**
UKCA marking	**Yes**	D4i certified (DALI)	**No**
EU RoHS compliant	**Yes**	Light source energy efficiency class	**C**

STANDARDS & SUSTAINABILITY

Applicable standard	**EN-IEC 62722-2-1**	ETIM Class	**EC002892**
D-Mark (EN 60598-2-24)	**Yes**	Non-virgin material ratio	**Not determined**
Sustainability rating	**Not determined**	EAN / UPC	**Not determined**
Application areas	**Industry, warehouses, parkings, general lighting**		

Environmental data. Embedded carbon, recyclable content and sustainability ratings are provided per article where determined.

Documents. Photometric files (IES / LDT) and installation instructions are available at takton.ee.