DCW117 120 8200LM 51W 840 I OP PC IP65 MS

Symmetric · 4000 K · IP65 · IK10 · White



APPLICATION

DCW117 is a slim IP65 waterproof LED luminaire for warehouses, production facilities, technical rooms, parking garages and other industrial or utility spaces. Its modular design allows individual luminaires to be connected into continuous lighting lines, combining the flexibility of a trunking system with the simplicity of a standalone waterproof luminaire. The durable polycarbonate housing and diffuser provide reliable protection and long-term performance, while the compact profile is designed for fast installation. Available options include DALI-2, emergency lighting, through-wiring and various mounting configurations.

8200 lm	51 W	161 lm/W	4000 K	≥80	IP65	IK10	50 000 h
SYSTEM FLUX	INPUT POWER	EFFICACY	CCT	CRI	INGRESS	IMPACT	L90B10

ELECTRICAL PARAMETERS

Nominal supply voltage	230 (220–240) V AC	Supply voltage range	198–264 V AC
Type of supply current	AC	Supply frequency	50–60 Hz
Rated input power	51W	Power factor (PF)	0.95
Driver efficiency at nominal load	92%	Total harmonic distortion (THDi)	< 10% @ full load
Protection class (electric shock)	I	Surge protection (CM / DM)	4/2 kV
Driver type	TCI	Number of luminaires on MCB 16A type B	45

PHOTOMETRIC PARAMETERS

Luminous flux — system	8200lm	Luminous flux — LED module	9150lm
Luminous efficacy — system	161lm/W	Correlated colour temperature (CCT)	4000 K
Colour rendering index Ra (CRI)	≥80	Init. CRI tolerance	±3
Light distribution type	Symmetric	Luminaire beam spread	120.0°
Optic type	N/A	Light output ratio (LOR)	0.85
Photobiological safety class	RG0	Flicker — Output PstLM / SVM	≤0.1 / ≤0.2
Colour consistency (SDCM)	< 3 MacAdam steps	Upward light output ratio (ULOR)	N/A
Luminous flux tolerance	±5 %		

CONSTRUCTION & MATERIALS

Luminaire type	Dust/Waterproof	Light source type	LED
Light source replaceable	yes	Cap / base type	Integrated
Housing material	Polycarbonate	Reflector material	N/A
Housing coating	N/A	Optic material	PC
Optical cover material	N/A	Housing colour (RAL)	White
Mounting type	Surface, suspended	Cutout size	N/A
Overall dimensions (H × W × L)	75x63x1230	Weight (net)	2.4kg
Effective projected area	N/A	Windage projection area (side / below)	N/A
Number of light sources	1 pcs	Number of gear units	1 pcs

PROTECTION & ENVIRONMENT

IP rating — enclosure	IP65	Impact resistance class IK	IK10
Operating temperature range	-40...+35 °C	Storage temperature range	-40...+65 °C
Glow-wire test	650 °C / 5 s	Relative humidity (max)	N/A

CONTROL & DIMMING

Dimmable	**No**	Control protocol / interface	**on/off**
Dimming range	**N/A**	Built-in motion / presence sensor	**Yes**

RELIABILITY & LIFETIME

Light source lifetime	**50000 @ L80 B10h**	Lumen maintenance @ 50 000 h	**L80B10**
Lumen maintenance @ 100 000 h	**L70 B10**	Control gear failure rate @ 50 000 h	**5 %**
Control gear failure rate @ 100 000 h	**10 %**	Maximum case temperature Tc	**75°C**

CERTIFICATIONS

Warranty period	**5 years**	CE marking	**Yes**
ENEC mark	**No**	ENEC+ mark	**No**
UKCA marking	**Yes**	D4i certified (DALI)	**No**
EU RoHS compliant	**Yes**	Light source energy efficiency class	**C**

STANDARDS & SUSTAINABILITY

Applicable standard	**EN-IEC 62722-2-1**	ETIM Class	**EC002892**
D-Mark (EN 60598-2-24)	**Yes**	Non-virgin material ratio	**Not determined**
Sustainability rating	**Not determined**	EAN / UPC	**Not determined**
Application areas	**Industry, warehouses, parkings, general lighting**		

Environmental data. Embedded carbon, recyclable content and sustainability ratings are provided per article where determined.

Documents. Photometric files (IES / LDT) and installation instructions are available at takton.ee.