


DTP104 3250lm 27W 930 35DG WH DALI

Symmetric · 3000 K · IP20 · IK02 · White

**APPLICATION**

Optispot M DTP104 is a professional track-mounted LED spotlight combining compact dimensions with high light output and excellent visual quality. With CRI above 90 and efficacy up to 130 lm/W, it provides accurate colour reproduction while maintaining low energy consumption. Interchangeable optical options with 15°, 36° and 60° beam angles allow the luminaire to be used for focused accents, product displays or wider general illumination. The adjustable die-cast aluminium body is available in black or white and incorporates the driver directly into the track adaptor. DTP104 is an efficient and flexible solution for shops, showrooms, galleries, hospitality areas and modern commercial interiors.

3250 lm SYSTEM FLUX	27 W INPUT POWER	120 lm/W EFFICACY	3000 K CCT	≥90 CRI	IP20 INGRESS	IK02 IMPACT	50 000 h L90B10
-------------------------------	----------------------------	-----------------------------	----------------------	-------------------	------------------------	-----------------------	---------------------------

ELECTRICAL PARAMETERS

Nominal supply voltage	230 (220–240) V AC	Supply voltage range	220–240 V AC
Type of supply current	AC	Supply frequency	50 / 60 Hz
Rated input power	27W	Power factor (PF)	0.95
Total harmonic distortion (THDi)	<10%	Protection class (electric shock)	II
Driver type	Track adaptor driver		

PHOTOMETRIC PARAMETERS

Luminous flux — system	3250lm	Luminous efficacy — system	120lm/W
Correlated colour temperature (CCT)	3000 K	Colour rendering index Ra (CRI)	≥90
Init. CRI tolerance	±3	Light distribution type	Symmetric
Luminaire beam spread	35°	Optic type	PC / aluminium-coated optic
Photobiological safety class	RG1	Colour consistency (SDCM)	< 3 MacAdam steps
Upward light output ratio (ULOR)	0	Luminous flux tolerance	±5 %

CONSTRUCTION & MATERIALS

Luminaire type	Track-mounted spotlight	Light source type	LED
Light source replaceable	Yes	Cap / base type	Integrated
Housing material	Aluminium	Housing coating	Powder-coated
Optic material	Polycarbonate / aluminium	Optical cover material	Polycarbonate / aluminium
Housing colour (RAL)	White	Mounting type	Track-mounted
Number of light sources	1	Number of gear units	1 pcs

PROTECTION & ENVIRONMENT

IP rating — enclosure	IP20	Impact resistance class IK	IK02
Operating temperature range	0...+35 °C	Storage temperature range	-40...+65 °C
Glow-wire test	650 °C / 5 s	Relative humidity (max)	N/A

CONTROL & DIMMING

Dimmable	Yes	Control protocol / interface	DALI
Dimming range	1–100 %	Auto-dimming (chronoSTEP)	No
Built-in motion / presence sensor	No	Built-in daylight sensor	No
LED lumen maintenance compensation (CLO)	No	ZHAGA / NEMA socket compatibility	No

RELIABILITY & LIFETIME

Constant Light Output (CLO)	No	Light source lifetime	50000 @ L80 B50 h
Lumen maintenance @ 50 000 h	L80 B50	Control gear failure rate @ 50 000 h	5 %

CERTIFICATIONS

Warranty period	5 years	CE marking	Yes
ENEC mark	No	ENEC+ mark	No
UKCA marking	Yes	D4i certified (DALI)	No
EU RoHS compliant	Yes	Light source energy efficiency class	D

STANDARDS & SUSTAINABILITY

Applicable standard	EN-IEC 60598-2-1	ETIM Class	Not determined
Recyclable content ratio	Not determined	Non-virgin material ratio	Not determined
Sustainability rating	Not determined	EAN / UPC	Not determined
Application areas	Shops, showrooms, meeting rooms, circulation areas and hospitality		

Environmental data. Embedded carbon, recyclable content and sustainability ratings are provided per article where determined.

Documents. Photometric files (IES / LDT) and installation instructions are available at takton.ee.