


Length **90 mm****APPLICATION**

DWL-S is a versatile square surface-mounted LED luminaire for general and utility lighting. The compact, understated design is well suited for parking garages, basements, staircases, corridors, warehouses and technical rooms. A choice of PMMA or impact-resistant PC diffuser ensures soft, uniform illumination and allows the luminaire to be adapted to different operating conditions. IP65 protection, efficiency up to 120 lm/W and optional DALI control, motion sensor or three-hour emergency lighting make DWL-S a reliable and economical solution for both new installations and refurbishment projects.

2200 lm SYSTEM FLUX	18 W INPUT POWER	122 lm/W EFFICACY	4000 K CCT	≥80 CRI	IP65 INGRESS	IK10 IMPACT	50 000 h L90B10
-------------------------------	----------------------------	-----------------------------	----------------------	-------------------	------------------------	-----------------------	---------------------------

ELECTRICAL PARAMETERS

Nominal supply voltage	230 (220–240) V AC	Supply voltage range	220–240 V AC
Type of supply current	AC	Supply frequency	50 / 60 Hz
Rated input power	18W	Power factor (PF)	0.93
Driver efficiency at nominal load	0.87	Total harmonic distortion (THDi)	<10%
Protection class (electric shock)	I	Inrush current / time	5A 50µsec
Driver type	Philips / TCI	Number of luminaires on MCB 16A type B	50

PHOTOMETRIC PARAMETERS

Luminous flux — system	2200lm	Luminous flux — LED module	2500lm
Luminous efficacy — system	122lm/W	Correlated colour temperature (CCT)	4000 K
Colour rendering index Ra (CRI)	≥80	Init. CRI tolerance	±3
Light distribution type	Symmetric	Luminaire beam spread	Wide beam
Optic type	OP	Photobiological safety class	RG0
Flicker — Output PstLM / SVM	≤0.1 / ≤0.2	Colour consistency (SDCM)	< 3 MacAdam steps
Upward light output ratio (ULOR)	0	Luminous flux tolerance	±5 %

CONSTRUCTION & MATERIALS

Luminaire type	Surface-mounted luminaire	Light source type	LED
Light source replaceable	No	Cap / base type	Integrated
Housing material	PMMA	Optic material	Polycarbonate
Optical cover material	Polycarbonate	Housing colour (RAL)	White
Mounting type	Surface-mounted	Overall dimensions (H × W × L)	90x300x300
Weight (net)	2.0 kg	Number of gear units	1 pcs

PROTECTION & ENVIRONMENT

IP rating — enclosure	IP65	Impact resistance class IK	IK10
Operating temperature range	-40...+35 °C	Storage temperature range	-40...+65 °C
Glow-wire test	650 °C / 5 s	Relative humidity (max)	N/A

CONTROL & DIMMING

Dimmable	No	Control protocol / interface	On/off
Dimming range	N/A	Built-in motion / presence sensor	No
Built-in daylight sensor	No		

RELIABILITY & LIFETIME

Light source lifetime	50000 @ L80 B10 h	Lumen maintenance @ 50 000 h	L80 B10
Control gear failure rate @ 50 000 h	5 %	Control gear failure rate @ 100 000 h	10%
Maximum case temperature Tc	75°C		

CERTIFICATIONS

Warranty period	5 years	CE marking	Yes
ENEC mark	No	ENEC+ mark	No
UKCA marking	Yes	D4i certified (DALI)	No
EU RoHS compliant	Yes	Light source energy efficiency class	C

STANDARDS & SUSTAINABILITY

Applicable standard	EN-IEC 60598-2-1	ETIM Class	Not determined
Recyclable content ratio	Not determined	Non-virgin material ratio	Not determined
Sustainability rating	Not determined	EAN / UPC	Not determined
Application areas	Parking garages, basements, staircases, corridors, warehouses and technical rooms		

Environmental data. Embedded carbon, recyclable content and sustainability ratings are provided per article where determined.

Documents. Photometric files (IES / LDT) and installation instructions are available at takton.ee.